

ALTO

LED STRIP STR-ALTO



POWER

PROFILE / LUMINOUS FLUX



11W	11.2W / metre	SD · 1060 lm / metre	RD · 1190 lm / metre	P17D · 1010 lm / metre	P17R · 1010 lm / metre
16W	16.8W / metre	SD · 1590 lm / metre	RD · 1820 lm / metre	P17D · 1540 lm / metre	P17R · 1540 lm / metre
33W	33.6W / metre	N/A	N/A	P17D · 2800 lm / metre	P17R · 2800 lm / metre

COLOUR TEMPERATURE

2700K

3000K

4000K



sales@coolon.com.au

aus. 1300 287 533

intl. +613 8681 3633


www.coolon.com.au

Version 1.00


All documentation is subject to change without notice. Refer to our website for the latest information.

DIMENSIONS


SD Standard Profile




RD Reinforced Profile



P17D P17 Profile



P17R P17 Recessed Profile



ORDERING EXAMPLE

STR-ALTO	16W	3.0K	S2A0	P17D	WHT	WR2BS 100	IP40	
TYPE	WATTAGE	CCT	SEGMENTS	PROFILE / DIFFUSER	PROFILE COLOUR	WIRING CONFIG.	WIRING LENGTH	IP RATING

WATTAGE

<input type="checkbox"/> 11W	11.2W per Metre
<input type="checkbox"/> 16W	16.8W per Metre
<input type="checkbox"/> 33W	33.6W per Metre

COLOUR TEMPERATURE *

<input type="checkbox"/> 2.7K	2700K CRI 80
<input type="checkbox"/> 2.7KCRI	2700K CRI 90
<input type="checkbox"/> 3.0K	3000K CRI 80
<input type="checkbox"/> 3.0KCRI	3000K CRI 90
<input type="checkbox"/> 4.0K	4000K CRI 80
<input type="checkbox"/> 4.0KCRI	4000K CRI 90

PRODUCT LENGTH

<input type="checkbox"/> Length as per Site Measurements
<input type="checkbox"/> Length:
<input type="checkbox"/> Undefined

PROFILE / DIFFUSER **

<input type="checkbox"/> SD	Standard Profile Diffused
<input type="checkbox"/> RD	Reinforced Profile Diffused
<input type="checkbox"/> P17D	P17 Profile Diffused
<input type="checkbox"/> P17T	P17 Profile Diffused (IP65 Outdoor)
<input type="checkbox"/> P17R	P17 Recessed Profile Diffused

PROFILE COLOUR ***

<input type="checkbox"/> WHT	White (Standard)
<input type="checkbox"/> BLK	Black
<input type="checkbox"/> CST	Custom Colour

WIRING CONFIGURATION

<input type="checkbox"/> WR2OS	Wire 2 Core One Side
<input type="checkbox"/> WR2BS	Wire 2 Core Both Sides
<input type="checkbox"/> OC2MO	Outdoor Connector 2 pin Male Only
<input type="checkbox"/> OC2MF	Outdoor Connector 2 pin Male + Female
<input type="checkbox"/> SMPLC	Sample Type Connector 2.5mm

WIRING LENGTH

<input type="checkbox"/> 100	100mm
<input type="checkbox"/> 250	250mm
<input type="checkbox"/> 500	500mm
<input type="checkbox"/> 1000	1000mm

IP RATING

<input type="checkbox"/> IP40	Indoor Use
<input type="checkbox"/> IP65	Outdoor Use
<input type="checkbox"/> IP68	Prolonged Immersion Use

* Other CCT subject to availability.

** Low Profile not available in Uniform Glow.

*** Profile colour applicable to P17 and P17R only. Custom colours available on request.