


PRIMO

LED STRIP STR-PRIMO



POWER

PROFILE / LUMINOUS FLUX



10W 10.8W / metre

SD · 800 lm / metre

RD · 670 lm / metre

P17D · 570 lm / metre

COLOUR TEMPERATURE

2700K

3000K

4000K

5000K



sales@coolon.com.au

aus. 1300 287 533

intl. +613 8681 3633


www.coolon.com.au

Version 1.00


All documentation is subject to change without notice. Refer to our website for the latest information.

DIMENSIONS


SD Standard Profile



RD Reinforced Profile



P17D P17 Profile



ORDERING EXAMPLE

STR-MULTO	9W	3.0K	S2A0	P17D	WHT	WR2BS	100	IP40
TYPE	WATTAGE	CCT	SEGMENTS	PROFILE / DIFFUSER	PROFILE COLOUR	WIRING CONFIG.	WIRING LENGTH	IP RATING

COLOUR TEMPERATURE *

- 2.7K 2700K
- 3.0K 3000K
- 4.0K 4000K
- 5.0K 5000K

PRODUCT LENGTH

- Length as per Site Measurements
- Length:
- Undefined

* Other CCT subject to availability.

** Profile colour applicable to P17 only.
Custom colours available on request.

PROFILE / DIFFUSER

- SD Standard Profile Diffused
- RD Reinforced Profile Diffused
- P17D P17 Profile Diffused
- P17T P17 Profile Diffused (IP65 Outdoor)

PROFILE COLOUR **

- BLK Black (Standard)
- WHT White
- CST Custom Colour

WIRING CONFIGURATION

- WR2.1OS Wire 2+1 Core One Side
- WR2.1BS Wire 2+1 Core Both Sides
- WR4.1OS Wire 4+1 Core One Side
- WR4.1BS Wire 4+1 Core Both Sides
- OC2.1MO Outdoor Connector 2+1 pin Male Only
- OC2.1FO Outdoor Connector 2+1 pin Female Only
- OC2.1MF Outdoor Connector 2+1 pin Male + Female
- OC4.1MO Outdoor Connector 4+1 pin Male Only
- OC4.1FO Outdoor Connector 4+1 pin Female Only
- OC4.1MF Outdoor Connector 4+1 pin Male + Female
- SMP LC.1 Sample Type Connector 2.5mm

IP RATING

- IP40 Indoor Use
- IP65 Outdoor Use
- IP68 Prolonged Immersion Use