







Liverpool is a fully illuminated pole-top light column available in four length options and a range of colour temperatures. Featured in award-winning lighting projects, Liverpool transforms and enhances public and architectural spaces through its spectacular display of light and prominent form.

POWER	LUMINOUS FLUX	
56W 56W / metre		
COLOUR TEMPERATURE		
3	200K	4000K



CREATE DISTINCTIVE EFFECTS

Available in a range of heights and colour temperatures, this striking marker light can provide the sculptural effect and atmosphere you choose, punctuating outdoor spaces with a seamless warm glow or pillars of clear white.



360° ILLUMINATION

Liverpool is a pole-top light column that provides uniform illumination in 360 degrees. A bold feature alone or arranged in combination, Liverpool is a vibrant beacon that adds presence to urban spaces such as streets, roads and public areas, marking these spaces with a prominent display of light.



LONG USEFUL OPERATING LIFE

Coolon products use the world's most reputable LED manufacturers and the latest available standards to adequately report lumen maintenance. We strive to drive LEDs under their nominal current and use state-of-the-art heat dissipation methods, leading to durable electronics.



VARIOUS CCT & COLOUR BINNING CONSISTENCY

All products are offered in various colour temperatures, and manufactured using tighter bins, ensuring excellent consistency and uniformity.



5 YEARS WARRANTY

Coolon Luminaires are covered by a solid comprehensible manufacturer's warranty that covers a range of possible defects and performance parameters throughout the duration of the warranty period.



PROUDLY MADE IN AUSTRALIA

Our products are designed and manufactured in Australia. Engineered to perfection, using only the highest quality components and highly skilled labour, each luminaire is assembled and thoroughly tested to ensure that it exceeds the highest standards.



TECHNICAL SPECIFICATIONS

Part Number		PLE-LIVERPOOL-10		
Description	Liverpool Static Whit	e Pole-top LED		
Length (Illuminated)	532.5mm	1,020mm	1,522.5mm	2,010mm
Width	105mm	105mm	105mm	105mm
Operating Voltage	24V	24V	24V	24V
Typical Power Consumption	28W	56W	84W	112W
Ambient Operating Temperature	Ta -10 to +50°C			
Avg Lumen Maint. @ Ta 25°C	70% @ 50,000 Hours	6		
IP Rating	IP65			

• IP RATING



Fully protected against dust. Protected against water jets from all directions.





¹ Maximum distance from driver to luminaire is 15,000mm with the provided 2 core AWG14





PLE - LIVERPOOL	- 3	.2K	-	10	-	GRY	-	IP65
TYPE		T		T		Ţ		Ţ
COLOUR TEMPERATURE								
FULL PRODUCT LENGTH								
BASE COLOUR								
IP RATING								

COLOU	R TEMPERATURE
3.2K	3200K
4.0K	4000K
FULL P	RODUCT LENGTH
FULL P	RODUCT LENGTH 798.5mm
05	798.5mm

BASE COLOUR		
GRY	Grey (Standard)	
BLK	Black	
WHT	White	
CST	Custom Colour 1	

IP RATING

IP65 Outdoor Use

¹ Custom colours available on request.

