

# PRIMO

LED STRIP STR-PRIMO



## POWER

## PROFILE / LUMINOUS FLUX



**SD**

**RD**

**P17D**

**PR17D**

**10W** 10.8W / metre

800 lm / metre

670 lm / metre

570 lm / metre

570 lm / metre

## COLOUR TEMPERATURE

2700K


3000K

4000K


5000K

## DIMENSIONS


**SD** • Standard Profile




**RD** • Reinforced Profile




**P17D** • P17 Profile



**P17T** • P17 Profile



**PR17D** • P17 Recessed Profile



## ORDERING EXAMPLE

**STR-PRIMO 3.0K S2A1 P17D BLK WR2.1BS 100 IP40**

TYPE CCT SEGMENTS PROFILE / DIFFUSER PROFILE COLOUR WIRING CONFIG. WIRING LENGTH IP RATING

### COLOUR TEMPERATURE <sup>1</sup>

2.7K	2700K
3.0K	3000K
4.0K	4000K
5.0K	5000K

### PRODUCT LENGTH <sup>2</sup>

Length as per Site Measurements
Length:
Undefined

### PROFILE / DIFFUSER

SD	Standard Profile Diffused
RD	Reinforced Profile Diffused
P17D	P17 Profile Diffused
PR17D	P17 Recessed Profile Diffused

### PROFILE COLOUR <sup>3</sup>

BLK	Black (Standard)
WHT	White
CST	Custom Colour

### WIRING CONFIGURATION

WR2.1OS	Wire 2+1 Core One Side
WR2.1BS	Wire 2+1 Core Both Sides
OC2.1MO	Outdoor Connector 2+1 pin Male Only
OC2.1MF	Outdoor Connector 2+1 pin Male + Female
SMPLC.1	Sample Type Connector 2.5mm

### WIRING LENGTH

100	100mm
250	250mm
500	500mm
1000	1,000mm

### IP RATING

IP40	Indoor Use
------	------------

<sup>1</sup> Other colour temperatures subject to availability.

<sup>2</sup> LD is only available for lengths up to 2,200mm.

<sup>3</sup> Profile colour applicable to P17 and PR17 only. Custom colours available on request.