

# SLIM

LED STRIP STR-SLIM



## POWER

## PROFILE / LUMINOUS FLUX



## SD

<b>7W</b>	7W / metre	400 lm / metre
<b>14W</b>	14W / metre	800 lm / metre

## COLOUR TEMPERATURE


2700K

3000K

4000K

## ■ DIMENSIONS

**SD** • Standard Profile



## ■ ORDERING EXAMPLE

<b>STR-SLIM</b>	<b>7W</b>	<b>3.0K</b>	<b>S2A1</b>	<b>SD</b>	<b>BLK</b>	<b>WR2BS</b>	<b>100</b>	<b>IP40</b>
TYPE	WATTAGE	CCT	SEGMENTS	PROFILE / DIFFUSER	PROFILE COLOUR	WIRING CONFIG.	WIRING LENGTH	IP RATING
<b>■ WATTAGE</b>								
7W	7W per Metre							
14W	14W per Metre							
<b>■ COLOUR TEMPERATURE</b>								
2.7K	2700K CRI 80							
2.7KCRI	2700K CRI 90							
3.0K	3000K CRI 80							
3.0KCRI	3000K CRI 90							
4.0K	4000K CRI 80							
4.0KCRI	4000K CRI 90							
<b>■ PRODUCT LENGTH</b>								
Length as per Site Measurements								
Length:								
Undefined								
<b>■ PROFILE / DIFFUSER</b>								
SD	Standard Profile Diffused							
<b>■ PROFILE COLOUR</b>								
BLK	Black (Standard)							
GRY	Grey							
<b>■ WIRING CONFIGURATION</b>								
WR2OS	Wire 2 Core One Side							
WR2BS	Wire 2 Core Both Sides							
SMPLC	Sample Type Connector 2.5mm							
<b>■ WIRING LENGTH</b>								
100	100mm							
250	250mm							
500	500mm <sup>1</sup>							
1000	1,000mm <sup>1</sup>							
<b>■ IP RATING</b>								
IP40	Indoor Use							

<sup>1</sup> Only applicable to WR2OS and WR2BS