


# MULTO

LED STRIP STR-MULTO



## POWER

## PROFILE / LUMINOUS FLUX




		SD	RD	P17D	PR17D
<b>9W</b>	9.6W / metre	297 lm / metre	265 lm / metre	334 lm / metre	334 lm / metre
<b>16W</b>	16W / metre	693 lm / metre	619 lm / metre	620 lm / metre	620 lm / metre

## COLOUR TEMPERATURE




## DIMENSIONS


**SD** • Standard Profile




**RD** • Reinforced Profile




**P17D** • P17 Profile



**P17T** • P17 Profile



**PR17D** • P17 Recessed Profile



## ORDERING EXAMPLE

STR-MULTO	9W	3.0K	S2A0	P17D	WHT	WR2BS	100	IP40										
TYPE	WATTAGE	CCT	SEGMENTS	PROFILE / DIFFUSER	PROFILE COLOUR	WIRING CONFIG.	WIRING LENGTH	IP RATING										
<p>■ <b>WATTAGE</b></p> <table border="1"> <tr> <td>9W</td> <td>9.6W per metre</td> </tr> <tr> <td>16W</td> <td>16W per metre</td> </tr> </table>									9W	9.6W per metre	16W	16W per metre						
9W	9.6W per metre																	
16W	16W per metre																	
<p>■ <b>PROFILE COLOUR</b><sup>2</sup></p> <table border="1"> <tr> <td>WHT</td> <td>White (Standard)</td> </tr> <tr> <td>BLK</td> <td>Black</td> </tr> <tr> <td>CST</td> <td>Custom Colour</td> </tr> </table>									WHT	White (Standard)	BLK	Black	CST	Custom Colour				
WHT	White (Standard)																	
BLK	Black																	
CST	Custom Colour																	
<p>■ <b>COLOUR TEMPERATURE</b><sup>1</sup></p> <table border="1"> <tr> <td>2.7K</td> <td>2700K CRI 80</td> </tr> <tr> <td>3.0K</td> <td>3000K CRI 80</td> </tr> <tr> <td>3.2K</td> <td>3200K CRI 80</td> </tr> <tr> <td>4.0K</td> <td>4000K CRI 80</td> </tr> </table>									2.7K	2700K CRI 80	3.0K	3000K CRI 80	3.2K	3200K CRI 80	4.0K	4000K CRI 80		
2.7K	2700K CRI 80																	
3.0K	3000K CRI 80																	
3.2K	3200K CRI 80																	
4.0K	4000K CRI 80																	
<p>■ <b>WIRING CONFIGURATION</b></p> <table border="1"> <tr> <td>WR2OS</td> <td>Wire 2 Core One Side</td> </tr> <tr> <td>WR2BS</td> <td>Wire 2 Core Both Sides</td> </tr> <tr> <td>OC2MO</td> <td>Outdoor Connector 2 pin Male Only</td> </tr> <tr> <td>OC2MF</td> <td>Outdoor Connector 2 pin Male + Female</td> </tr> <tr> <td>SMPLC</td> <td>Sample Type Connector 2.5mm</td> </tr> </table>									WR2OS	Wire 2 Core One Side	WR2BS	Wire 2 Core Both Sides	OC2MO	Outdoor Connector 2 pin Male Only	OC2MF	Outdoor Connector 2 pin Male + Female	SMPLC	Sample Type Connector 2.5mm
WR2OS	Wire 2 Core One Side																	
WR2BS	Wire 2 Core Both Sides																	
OC2MO	Outdoor Connector 2 pin Male Only																	
OC2MF	Outdoor Connector 2 pin Male + Female																	
SMPLC	Sample Type Connector 2.5mm																	
<p>■ <b>PRODUCT LENGTH</b></p> <p>Length as per Site Measurements</p> <p>Length:</p> <p>Undefined</p>																		
<p>■ <b>WIRING LENGTH</b></p> <table border="1"> <tr> <td>100</td> <td>100mm</td> </tr> <tr> <td>250</td> <td>250mm</td> </tr> <tr> <td>500</td> <td>500mm</td> </tr> <tr> <td>1000</td> <td>1,000mm</td> </tr> </table>									100	100mm	250	250mm	500	500mm	1000	1,000mm		
100	100mm																	
250	250mm																	
500	500mm																	
1000	1,000mm																	
<p>■ <b>PROFILE / DIFFUSER</b></p> <table border="1"> <tr> <td>SD</td> <td>Standard Profile Diffused</td> </tr> <tr> <td>RD</td> <td>Reinforced Profile Diffused</td> </tr> <tr> <td>P17D</td> <td>P17 Profile Diffused</td> </tr> <tr> <td>PR17D</td> <td>P17 Recessed Profile Diffused</td> </tr> </table>									SD	Standard Profile Diffused	RD	Reinforced Profile Diffused	P17D	P17 Profile Diffused	PR17D	P17 Recessed Profile Diffused		
SD	Standard Profile Diffused																	
RD	Reinforced Profile Diffused																	
P17D	P17 Profile Diffused																	
PR17D	P17 Recessed Profile Diffused																	
<p>■ <b>IP RATING</b></p> <table border="1"> <tr> <td>IP40</td> <td>Indoor Use</td> </tr> </table>									IP40	Indoor Use								
IP40	Indoor Use																	

<sup>1</sup> Other CCT subject to availability.

<sup>2</sup> Profile colour applicable to P17 and PR17 only. Custom colours available on request.