

PRIMO X2



LED STRIP STR-PRIMO X2



POWER

PROFILE / LUMINOUS FLUX




	SD	LD	RD	P17D	PR17D
21W 21.6W / metre	1,400 lm / metre	1,590 lm / metre	1,570 lm / metre	1,330 lm / metre	1,330 lm / metre

COLOUR TEMPERATURE




DIMENSIONS


SD • Standard Profile




LD • Low Profile




RD • Reinforced Profile




P17D • P17 Profile



P17T • P17 Profile



PR17D • P17 Recessed Profile



ORDERING EXAMPLE

STR-PRIMO X2 3.0K S2A0 P17D BLK WR2.1BS 100 IP40

TYPE CCT SEGMENTS PROFILE / DIFFUSER PROFILE COLOUR WIRING CONFIG. WIRING LENGTH IP RATING

COLOUR TEMPERATURE ¹

2.7K	2700K
3.0K	3000K
4.0K	4000K
5.0K	5000K

PRODUCT LENGTH ²

Length as per Site Measurements
Length:
Undefined

PROFILE / DIFFUSER

SD	Standard Profile Diffused
LD	Low Profile Diffused
RD	Reinforced Profile Diffused
P17D	P17 Profile Diffused
PR17D	P17 Recessed Profile Diffused

PROFILE COLOUR ³

BLK	Black (Standard)
WHT	White
CST	Custom Colour

WIRING CONFIGURATION

WR2.1OS	Wire 2+1 Core One Side
WR2.1BS	Wire 2+1 Core Both Sides
OC2.1MO	Outdoor Connector 2+1 pin Male Only
OC2.1MF	Outdoor Connector 2+1 pin Male + Female
SMPLC.1	Sample Type Connector 2.5mm

WIRING LENGTH

100	100mm
250	250mm
500	500mm
1000	1,000mm

IP RATING

IP40	Indoor Use
------	------------

¹ Other colour temperatures subject to availability.

² LD is only available for lengths up to 2,200mm.

³ Profile colour applicable to P17 and PR17 only. Custom colours available on request.