





POWER	PROFILE / LUMINOUS FLUX						
	SD	P17D	PR17D				
15W 15.6W / metre	400 lm / metre	3					


RGB FULL COLOUR


COOLON

DIMENSIONS

SD · Standard Profile







32mm

 ORDERING EXAMPLE

STR-SP	ECTRUM	S2A1	P17D	BLK	WR4BS	100	IP40	
TYPE		SEGMENTS	PROFILE / DIFFUSER	PROFILE COLOUR	WIRING CONFIG.	WIRING LENGTH	IP RATING	
■ PRODUCT LENGTH				WIRING CONFIGURATION				
Length as per Site Measurements				WR4OS	Wire 4 Core One Side			
Length:				WR4BS	Wire 4 Core	Wire 4 Core Both Sides		
Undefined	I			OC4MO	Outdoor Co	nnector 4 pin	Male Only	
				OC4MF	Outdoor Co	nnector 4 pin	Male + Female	
PROFILE	/ DIFFUSER							
SD	Standard Profile Diffused			WIRING LENGTH				
P17D	P17 Profile Diffused			100	100mm			
PR17D PR17 Reces		sed Profile Diffused		250	250mm			
				500	500mm			
PROFILE COLOUR 1			1000	1,000mm				
BLK	Black (Standa	ard)						
WHT	White			IP RATIN	G			

CST Custom Colour

IP40 Indoor Use

¹ Profile colour applicable to P17 only. Custom colours available on request.

©:COOLON