


STRYDE

20W BATTEN




STRYDE 20W BATTEN



STRYDE is a versatile LED light designed for demanding environments. Featuring high-lumen SMD LEDs, a wide 120° beam, and a high-transmittance diffuser, it delivers uniform illumination. Its modular, plug-in design supports sensors, with surface or pendant mounting. Ideal for humid and dusty industrial applications.

DIMENSIONS (MM)

Surface Mount: 680 x 125 x 86 mm



PRODUCT INFO

Model	STRYDE
Range	Batten
Mounting Method	Surface Mount / Pendant Mount
Voltage	220-240VAC, 50Hz

PERFORMANCE SPECIFICATIONS

Power	4-Step Power Select: 20W/18W/15W/12W
Lumens	1,440 - 2,450 lm
Beam Angle	120°
IP Rating	IP65
IK Rating	IK08
LEDs	2835SMD CRI80
Dimmable	No
Working Temperature	-20°C to 45°C

DESIGN SPECIFICATIONS

Weight	0.95kg
Construction	PC
Diffuser Material	PC
Housing Colour	Grey
Sensor	Microwave Sensor (Optional upgrade)

COMPLIANCE & WARRANTY

Certificates Approvals	AS2293- AS/NZS CISPR 15
Warranty	5 Year Warranty

ORDERING EXAMPLE

STRYDE	B0	2	20	PS4	WNC	NS	A
MODEL	STANDBY POWER	BODY TYPE	POWER	POWER SELECTION	COLOUR TEMPERATURE	SENSOR	VOLTAGE
STRYDE	B0 No standby battery	2 600mm	20 20W	PS4 4-Step Power Select	WNC Warm-Neutral-Cool White	NS No Sensor MS Microwave Sensor (Optional upgrade)	A 220-240VAC, 50Hz